

LATCH Manual Update Related to the
Honda Passport, MY19-20, Lexus UX, MY19
Toyota Prius V, MY12-18, Toyota Yaris, MY06-19
Toyota Yaris iA, MY15-19 Toyota Sienna, MY11-19
2019-2020 LM Updates Page, www.saferidenews.com

Page B-108, Honda

PASSPORT	SUV	19-20	LATCH	(2) LATCH	(3) TAs on backs of seats Owner's Manual (OM) Clarification: Some MY19 OMs indicate that only the onboard positions of the 2nd row are equipped with LATCH; in fact, there is also a standard LATCH system in the center seating position, as well.
----------	-----	-------	-------	-----------	---

Page B-139, Lexus

UX	Crossover	19	TA	(2) LATCH	(3) TAs on backs of seats Center: May borrow inner LA bars of outboard LATCH to install CR. If used for center, LAs may not be used for either OB position. Space between inner LAs is 15.6 inches (396 mm). Head Restraints (HRs): To tether, route a 2-point (single-strap) tether over the center of the HR, and a 3-point (V-shaped) tether around each side. Owner's Manual (OM) Clarification: Although some OMs do not state that a CR may be installed in the center seating position using LATCH, the vehicle manufacturer says it IS safe to install a CR there, per the notes above, and that doing so is approved IF proper installation is achieved.
----	-----------	----	----	-----------	---

Page B-208, Toyota

PRIUS V	4-door Wagon	12-18	TA	(2) LATCH	(3) TAs on backs of seats. TAs are lower on seatback than cargo area floor. Slide vehicle seat forward to hook tether to TA, then return it to its rear-most position to install CR. Lower Anchors: Bars are below the bight, in zippered vertical slits in the vehicle upholstery. Find LA photos at www.saferidenews.com , LATCH Gallery. Vehicle Seatback: Put the seatback in the first locked position to install a CR with LATCH. MY18: In this model year, this model sold in Canada only.
---------	--------------	-------	----	-----------	---

LATCH Manual Update Related to the
Honda Passport, MY19-20, Lexus UX, MY19
Toyota Prius V, MY12-18, Toyota Yaris, MY06-19
Toyota Yaris iA, MY15-19 Toyota Sienna, MY11-19
2019-2020 LM Updates Page, www.saferidenews.com

Page B-213, Toyota

YARIS	HB	06-19	TA	(2) LATCH	(3) TAs on backs of seats, near or below cargo floor. To improve access to TAs, slide seat forward. Find TA photos at www.saferidenews.com , LATCH Gallery. Cargo Cover: If cargo cover is installed, remove to access tether anchor. Reinstall after tether installation. Head Restraints (HRs): To tether, remove and securely stow HR; replace HR when CR is uninstalled. (Exception: For MY06-11 vehicles with non-split seat option, reinstall HR after attaching tether.) Vehicle Seatback, MY06-11: Put the seatback in the first locked position to install a CR. MY19: In this model year, this model sold in Canada only.
	4-door Sedan	06-12	TA	(2) LATCH	(3) TAs on rear filler panel Head Restraints (HRs), MY06-10: To tether, remove and securely stow HR; replace the HR when CR is uninstalled. Head Restraints (HRs), MY11-12: To tether, lift HR and route tether under it. Return HR to lowest locked position after tether is attached. Split Vehicle Seatback, MY06-11: Put the seatback in the first locked position to install a CR.
		16-19	TA	(2) LATCH	(3) TAs on rear filler panel Center, MY16 and Newer (Canada) and MY19 and newer (U.S.): May borrow inner LA bars of outboard LATCH to install CR. If used for center, LAs may not be used for either outboard position. Space between inner LAs is 14.2 inches (360 mm). Head Restraints (HRs): Remove and securely stow HR (regardless of whether tether is used). Replace the HR when CR is uninstalled.
YARIS iA	4-door Sedan	17-18	TA	(2) LATCH	(3) TAs on rear filler panel Center: May borrow inner LA bars of outboard LATCH to install CR. If used for center, LAs may not be used for either outboard position. Space between inner LAs is 14.2 inches (360 mm). Head Restraints (HRs): Remove and securely stow HR (regardless of whether tether is used). Replace the HR when CR is uninstalled. Note: In MY17, the Scion iA became the Yaris iA and both Yaris and Yaris iA were sold in MY17-18. In MY19, Yaris iA became the Yaris. See Scion iA in this appendix for MY16 vehicles.

LATCH Manual Update Related to the
Honda Passport, MY19-20, Lexus UX, MY19
Toyota Prius V, MY12-18, Toyota Yaris, MY06-19
Toyota Yaris iA, MY15-19 Toyota Sienna, MY11-19
2019-2020 LM Updates Page, www.saferidenews.com

Page B-217, Toyota

SIENNA Van	11-14	7-passenger: N/A 8- passenger: None	(2) LATCH	LATCH (offset to outboard- behind- driver side)	None	<p>(3) TAs (MY11-14) or (4) TAs (MY15-19) on backs of seats; to find unlabeled 3rd row TA, lift flap at lower back of seatback. DO NOT use 3rd row cargo anchors as TAs.</p> <p>Vehicle Seatback: Find photos at www.saferidenews.com, LATCH Gallery. To install a CR with LATCH:</p> <p>2nd Row and 3rd Row Manual Seat: Recline the seatback, as described in the OM, to expose the lower anchors in the seat bight. Once the LA connectors are attached to the LAs, it is permissible to adjust the vehicle seatback to a more upright position that provides a good CR-to-vehicle-seat fit, as defined in the NHTSA or CPSAC standardized curriculum.</p> <p>3rd Row Power Seat: Raise seatback to its upright position by pressing the seatback angle adjustment switch.</p> <p>Head Restraints (HRs): MY11-14: To tether, lift HR and route tether under it. Return HR to lowest position after tether hook is attached. MY15-19,, 2nd Row and 3rd Row, Center: To tether, lift HR and route tether under it. Return HR to lowest position after tether hook is attached. MY15-19, 3rd Row, Outboard-Behind-Passenger: To tether, lift HR and route tether under it. Auto Access Seat option: Do NOT install a CR using a seat belt switched to ALR mode.</p>
	15-19				Behind- passenger side: LATCH	